

R580

Product Description

Features

Bona R580 is water and solvent free silane based compound for priming and/or sealing the residuele moisture in the substrate (up to 5%CM. / 90%RH.) before installing a wooden floor. Optimal to apply prior Bona R850, R850T. Also compatible with other Bona Silan based wooden floor adhesives like Bona R845 or Bona R860.

Remark: Bona R860 and R845 have a higher water permeability. Suitable to apply before using Bona levelling compounds. Please note that while the adhesives are applied direct on the primer, levelling compounds need a broadcasting of sand in the wet primer.

- One-Component
- Single coat application
- Fast setting
- Trowel easy application
- Can be used as a two component system to gain even shorter setting time by adding and mixing 1 weight % water
- Not hazardous, safe handling and transport without constraints

Technical Data

Product type: Silane based

Colour: White

Viscosity: Easy to apply – self levelling

Density: 1,25 g/cm³

Cleaning agents: S100, acetone, ethanol, white spirit. Set material can only be removed mechanical.

Storage / transport: The temperature must not fall below +5°C or exceed +25°C during storage and transport.

Store in a dry, well ventilated place.

Shelf life: 6 months. If the product has settled out after longer storage times, stir thoroughly prior to use.

Pack size:

One component- net 7 kg per bucket (60 per pallet)

Two component-net 6 kg per bucket (60 per pallet)

including a bag with water (60 gramm), to be used as a 2nd component.

Safety

According to EU-law the product is not hazardous.

Additional detailed information is noted in the appropriate Safety Data Sheet