



Provided that our Storage Maintenance and Fitting Instructions are followed at all times the Product has the following

Solid Oak Drawer Handle Product Specification & Technical Data Sheet

Product Code: CRD-200- Drawer Handle

Solid Oak Drawer Handle LACQUER FINISH



Sustainability:

The Solid Wood Flooring products are not listed in CITES Appendices or on the IUCN Red List of Threatened Species.

This is an ethically sustainable sourced engineered timber wood floor designed for use as an interior floor finish.

Engineered wood floors are more sustainable than solid and minimise the impact on valuable resources. The construction means that these wood floors are more stable than solid floors.

Product Details

Wood type:	<i>Solid White Oak – Quercus SPP.</i>
Size:	<i>30mm wide x 200mm long x 20mm thick</i>
Finish:	<i>Matt UV Lacquered</i>
Process :	<i>Scalloped back with two screws</i>
Length:	<i>200mm</i>
Screw Length:	<i>24mm (to fit 18mm thick cabinetry carcass)</i>
Pattern:	<i>Smooth surface finish</i>
Edge Profile:	<i>Pencil Edge</i>
Grade:	<i>AB Select Grade</i>
Packing:	<i>Each box size is 125mm wide x 210mm long x 185mm high with 6 boxes packed in one large one whose size is 485wide x 430 long x 190mm high weighing 20kgs. Total number of handles = 240 + 480 screws</i>
Weight:	<i>Each carton will weigh approx. 20kgs</i>
Certification:	<i>FSC 100%.</i>

Fixing: See our Storage Fitting and Maintenance Instructions part of our T&C's

All wood Flooring products should be fitted in accordance with BS8201:2011

NBS:

NBS specifications can be written by request once we have full details of the subfloor build up.

Cleaning: See our Storage Fitting and Maintenance Instructions part of our T&C's

(never use solvent cleaning solution) *Correct cleaning and maintenance is important. Contamination from paints, whether oil or acrylic based will prove to be difficult to remove without damaging the wood surface. If any paint finds its way onto the wood surface, then BEFORE it completely dries, gentle rubbing with a non-alcoholic wipe might soften and remove the paint - but once the paint has dried it will be almost impossible to remove.*

BRE Green Guide:

A generic product of this type would correspond to Element Number 1321580001 of the BRE Green Guide 2008 ratings and achieve a rating of A+. The actual Kg/m² achieved will be dependent on the type of fitting chosen. The Solid Wood Flooring Company recommend that as a basis for achieving this result all fitting must conform to BS8201:2011

Health & Safety:

Solid Oak Drawer Handles are a natural product and on its own offers no recognisable health and safety risks. When re-manufacturing any wood product please follow HSE advice.

Company Approvals:

The Solid Wood Flooring Company operate a stringent sustainable environmental policy, details of which can be seen on the web site. We are certified by all the relevant organisations and our certificate numbers can be seen below. In addition to this we also adhere to the TTF responsible purchasing policy at all times. Below are our credentials::

Members of The Timber Trade Federation

Operate and are audited to the TTF Responsible Purchasing Policy

FSC - Solid Wood Flooring Certificate Code: RA-COC-005535

FSC - Solid Wood Flooring License Number: FSC-C007915

FSC - Solid Wood Flooring Chain of Custody Number: RA-COC-005535 HA

PEFC - Solid Wood Flooring Licence Number: PEFC/16-37-1814

PEFC - Solid Wood Flooring Certificate Number: CATG-FEFC-400-AT

WWF The Solid Wood Flooring Company achieved the highest - 3 Trees - accreditation
