

# SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 453/2010)

## SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product name : HARD WAXOIL

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

### 1.3. Details of the supplier of the safety data sheet

Registered company name : BLANCHON.

Address : 28, rue Charles Martin B.P. 105.69190.SAINT FONS.FRANCE.

Telephone : 00.33.4.72.89.06.09. Fax : 00.33.4.72.89.06.02.

fds@blanchon.com

### 1.4. Emergency telephone number : 00.33.1.45.42.59.59.

## SECTION 2 : HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Flammable liquid, Category 3 (Flam. Liq. 3, H226).

Repeated exposure may cause skin dryness or cracking (EUH066).

May produce an allergic reaction (EUH208).

Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).

Aspiration hazard, Category 1 (Asp. Tox. 1, H304).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Flammable (R 10).

May produce an allergic reaction.

Repeated exposure may cause skin dryness or cracking (R 66).

Vapours may cause drowsiness and dizziness (R 67).

This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

### 2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



Signal Word :

DANGER

Product identifiers :

EC 919-857-5 HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

Additional labeling :

EUH208 Contains 2-OXY-BUTANON. May produce an allergic reaction.

Hazard statements :

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

This Safety Data Sheet is prepared in accordance with  
Annex II to Regulation (EC) No 1907/2006

First editing date : 14/12/2001  
Date of last updating : 11/08/2011  
Validation date : 28/03/2014

- H336 May cause drowsiness or dizziness.  
 EUH066 Repeated exposure may cause skin dryness or cracking.  
 Precautionary statements - General :  
 P101 If medical advice is needed, have product container or label at hand.  
 P102 Keep out of reach of children.  
 P103 Read label before use.  
 Precautionary statements - Prevention :  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P240 Ground/bond container and receiving equipment.  
 P241 Use explosion-proof electrical/ventilating/lighting/.../equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.  
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves/protective clothing/eye protection/face protection.  
 Precautionary statements - Response :  
 P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
 P303 + P361 + P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
 P312 Call a POISON CENTER or doctor/physician if you feel unwell.  
 P331 Do NOT induce vomiting.  
 P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
 P403 + P235 Store in a well-ventilated place. Keep cool.  
 P405 Store locked up.  
 Precautionary statements - Disposal :  
 P501 Dispose of contents / container to an approved landfill.

### 2.3. Other hazards

The mixture does not contain any substances classified as 'Substances of Very High Concern' (SVHC) by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

## SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

#### Composition :

| Identification                                                                                                                         | (EC) 1272/2008                                                                                              | 67/548/EEC                                     | Note  | %               |
|----------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|------------------------------------------------|-------|-----------------|
| CAS: 64742-48-9<br>EC: 919-857-5<br>REACH: 01-2119463258-33<br>HYDROCARBONS, C9-C11, N-ALKANES,<br>ISOALKANES, CYCLICS, < 2% AROMATICS | GHS08, GHS07, GHS02<br>Dgr<br>Flam. Liq. 3, H226<br>Asp. Tox. 1, H304<br>STOT SE 3, H336<br>EUH:066         | Xn<br>Xn;R65<br>R10<br>R66-R67                 | P     | 50 <= x % < 100 |
| CAS: 8002-74-2<br>EC: 232-315-6<br>REACH: 01-2119488076-30-0007<br>PARAFFIN WAXES AND HYDROCARBON WAXES                                |                                                                                                             |                                                | [1]   | 2.5 <= x % < 10 |
| INDEX: 616-014-00-0<br>CAS: 96-29-7<br>EC: 202-496-6<br>REACH: 01-2119539477-28-0004<br>2-OXY-BUTANON                                  | GHS08, GHS05, GHS07<br>Dgr<br>Carc. 2, H351<br>Acute Tox. 4, H312<br>Eye Dam. 1, H318<br>Skin Sens. 1, H317 | Xn<br>Carc. Cat. 3;R40<br>Xn;R21<br>Xi;R41-R43 | [2]   | 0 <= x % < 2.5  |
| CAS: 22464-99-9<br>EC: 245-018-1<br>REACH: 01-2119979088-21<br>OCTANOIC ACID ZIRCONIUM SALT                                            | GHS08<br>Wng<br>Repr. 2, H361d                                                                              | Xn<br>Repr. Cat. 3;R63                         | F [2] | 0 <= x % < 2.5  |
| CAS: 64-17-5<br>EC: 200-578-6                                                                                                          | GHS07, GHS02<br>Dgr                                                                                         | Xi,F<br>Xi;R36                                 | [1]   | 0 <= x % < 2.5  |

This Safety Data Sheet is prepared in accordance with Annex II to Regulation (EC) No 1907/2006

First editing date : 14/12/2001  
 Date of last updating : 11/08/2011  
 Validation date : 28/03/2014

|                                                                                                |                                                                                               |                                    |     |                |
|------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------|------------------------------------|-----|----------------|
| REACH: 01-2119457610-43<br>ETHANOL                                                             | Flam. Liq. 2, H225<br>Eye Irrit. 2, H319                                                      | F;R11                              |     |                |
| INDEX: 603-117-00-0<br>CAS: 67-63-0<br>EC: 200-661-7<br>REACH: 01-2119457558-25<br>PROPAN-2-OL | GHS02, GHS07<br>Dgr<br>Flam. Liq. 2, H225<br>Eye Irrit. 2, H319<br>STOT SE 3, H336            | Xi,F<br>Xi;R36<br>F;R11<br>R67     | [1] | 0 <= x % < 2.5 |
| INDEX: 606-002-00-3<br>CAS: 78-93-3<br>EC: 201-159-0<br>REACH: 01-2119457290-43<br>BUTANONE    | GHS02, GHS07<br>Dgr<br>Flam. Liq. 2, H225<br>Eye Irrit. 2, H319<br>STOT SE 3, H336<br>EUH:066 | Xi,F<br>Xi;R36<br>F;R11<br>R66-R67 | [1] | 0 <= x % < 2.5 |
| CAS: 14808-60-7<br>EC: 238-878-4<br>QUARTZ                                                     |                                                                                               |                                    | [1] | 0 <= x % < 2.5 |

#### Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

[2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

Note P: The carcinogen or mutagen classification does not apply because the substance contains less than 0.1 % w/w of benzene (EINECS 200-753-7).

## SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

### 4.1. Description of first aid measures

#### In the event of exposure by inhalation :

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

In the event of an allergic reaction, seek medical attention.

#### In the event of splashes or contact with eyes :

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

#### In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

#### In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

If swallowed accidentally, do not allow to drink, do not induce vomiting and transfer to hospital immediately by ambulance. Show the label to the doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

No data available.

### 4.3. Indication of any immediate medical attention and special treatment needed

No data available.

## SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

This Safety Data Sheet is prepared in accordance with  
Annex II to Regulation (EC) No 1907/2006

First editing date : 14/12/2001  
Date of last updating : 11/08/2011  
Validation date : 28/03/2014

### 5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

#### Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO<sub>2</sub>)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

#### Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

### 5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

### 5.3. Advice for firefighters

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

---

## SECTION 6 : ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

#### For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

#### For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

### 6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

### 6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

### 6.4. Reference to other sections

No data available.

---

## SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

### 7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

#### Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

This Safety Data Sheet is prepared in accordance with  
Annex II to Regulation (EC) No 1907/2006

First editing date : 14/12/2001  
Date of last updating : 11/08/2011  
Validation date : 28/03/2014

Never inhale this mixture.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged : always earth during decanting operations. Wear antistatic shoes and clothing and floors should be electrically conductive.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

#### Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid inhaling vapors.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Packages which have been opened must be reclosed carefully and stored in an upright position.

#### Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

#### 7.2. Conditions for safe storage, including any incompatibilities

No data available.

#### Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from food and drink, including those for animals.

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

#### Packaging

Always keep in packaging made of an identical material to the original.

#### 7.3. Specific end use(s)

No data available.

## SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Occupational exposure limits :

- European Union (2009/161/EU, 2006/15/EC, 2000/39/EC, 98/24/EC)

| CAS     | VME-mg/m3 : | VME-ppm : | VLE-mg/m3 : | VLE-ppm : | Notes : |
|---------|-------------|-----------|-------------|-----------|---------|
| 78-93-3 | 600         | 200       | 900         | 300       | -       |

- France (INRS - ED984 :2008) :

| CAS        | VME-ppm : | VME-mg/m3 : | VLE-ppm : | VLE-mg/m3 : | Notes : | TMP No : |
|------------|-----------|-------------|-----------|-------------|---------|----------|
| 8002-74-2  | -         | 2           | -         | -           | -       | 36       |
| 64-17-5    | 1000      | 1900        | 5000      | 9500        | -       | 84       |
| 67-63-0    | -         | -           | 400       | 980         | -       | 84       |
| 78-93-3    | 200       | 600         | 300       | 900         | *       | 84       |
| 14808-60-7 | -         | 0.1 A       | -         | -           | -       | 25       |

- UK / WEL (Workplace exposure limits, EH40/2005, 2007) :

| CAS        | TWA :     | STEL :  | Ceiling : | Definition : | Criteria : |
|------------|-----------|---------|-----------|--------------|------------|
| 8002-74-2  | 2 mg/m3   | 6 mg/m3 | -         | -            | -          |
| 64-17-5    | 1000 ppm  | -       | -         | -            | -          |
| 67-63-0    | 400 ppm   | 500 ppm | -         | -            | -          |
| 78-93-3    | 200 ppm   | 300 ppm | -         | -            | -          |
| 14808-60-7 | 0.3 mg/m3 | -       | -         | -            | R          |

This Safety Data Sheet is prepared in accordance with Annex II to Regulation (EC) No 1907/2006

First editing date : 14/12/2001  
Date of last updating : 11/08/2011  
Validation date : 28/03/2014

## Derived no effect level (DNEL) or derived minimum effect level (DMEL):

OCTANOIC ACID ZIRCONIUM SALT (CAS: 22464-99-9)

Final use: Workers.

Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL : 6.49 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL : 32.97 mg of substance/m<sup>3</sup>

Final use: Consumers.

Exposure method: Ingestion.

Potential health effects: Long term systemic effects.

DNEL : 4.51 mg/kg body weight/day

Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL : 3.25 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL : 8.13 mg of substance/m<sup>3</sup>

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, &lt; 2% AROMATICS (CAS: 64742-48-9)

Final use: Workers.

Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL : 208 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL : 871 mg of substance/m<sup>3</sup>

Final use: Consumers.

Exposure method: Ingestion.

Potential health effects: Long term systemic effects.

DNEL : 125 mg/kg body weight/day

Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL : 125 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL : 185 mg of substance/m<sup>3</sup>

## Predicted no effect concentration (PNEC):

OCTANOIC ACID ZIRCONIUM SALT (CAS: 22464-99-9)

Environmental compartment: Soil.

PNEC : 1.06 mg/kg

Environmental compartment: Fresh water.

PNEC : 0.36 mg/l

Environmental compartment: Sea water.

PNEC : 0.036 mg/l

Environmental compartment: Fresh water sediment.

PNEC : 6.37 mg/kg

Environmental compartment: Marine sediment.

PNEC : 0.637 mg/kg

Environmental compartment: Waste water treatment plant.

PNEC : 71.7 mg/l

## 8.2. Exposure controls

## Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

#### - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

#### - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- PVA (Polyvinyl alcohol)

Recommended properties :

- Impervious gloves in accordance with standard EN374

#### - Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

#### - Respiratory protection

Avoid breathing vapours.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

---

## SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

#### General information :

Physical state : Fluid liquid.

#### Important health, safety and environmental information

pH : Not relevant.

Boiling point/boiling range : Not relevant.

Flash Point Interval : 23°C <= PE <= 55°C

Vapour pressure (50°C) : Below 110 kPa (1.10 bar).

Density : < 1

Water solubility : Insoluble.

Viscosity : 14 mm<sup>2</sup>/s < v <= 20,5 mm<sup>2</sup>/s (40°C)

Melting point/melting range : -20 °C.

Self-ignition temperature : 200 °C.

Decomposition point/decomposition range : Not relevant.

This Safety Data Sheet is prepared in accordance with  
Annex II to Regulation (EC) No 1907/2006

First editing date : 14/12/2001  
Date of last updating : 11/08/2011  
Validation date : 28/03/2014

## 9.2. Other information

V.O.C. 600g/l

---

## SECTION 10 : STABILITY AND REACTIVITY

### 10.1. Reactivity

No data available.

### 10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

### 10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

### 10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces

### 10.5. Incompatible materials

### 10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

---

## SECTION 11 : TOXICOLOGICAL INFORMATION

### 11.1. Information on toxicological effects

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Splashes in the eyes may cause irritation and reversible damage

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

Aspiration toxicity includes severe acute effects such as chemical pneumonia, varying degrees of pulmonary injury or death following aspiration.

#### 11.1.1. Substances

##### Acute toxicity :

PARAFFIN WAXES AND HYDROCARBON WAXES (CAS: 8002-74-2)

Oral route : LD50 > 5000 mg/kg

Species : Rat

OECD Guideline 401 (Acute Oral Toxicity)

Dermal route : LD50 > 2000 mg/kg

Species : Rat

OECD Guideline 402 (Acute Dermal Toxicity)

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS (CAS: 64742-48-9)

Oral route : LD50 > 5000 mg/kg

Species : Rat

OECD Guideline 401 (Acute Oral Toxicity)

Dermal route : LD50 > 5000 mg/kg

Species : Rabbit

OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route : LC50 > 5 mg/l

This Safety Data Sheet is prepared in accordance with  
Annex II to Regulation (EC) No 1907/2006

First editing date : 14/12/2001  
Date of last updating : 11/08/2011  
Validation date : 28/03/2014



Species : Rat

**Skin corrosion/skin irritation :**

PARAFFIN WAXES AND HYDROCARBON WAXES (CAS: 8002-74-2)

Corrosivity : No observed effect.

Species : Rabbit

OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

**Serious damage to eyes/eye irritation :**

PARAFFIN WAXES AND HYDROCARBON WAXES (CAS: 8002-74-2)

Conjunctival redness : Average score < 2

Species : Rabbit

OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Germ cell mutagenicity :**

PARAFFIN WAXES AND HYDROCARBON WAXES (CAS: 8002-74-2)

Mutagenesis (in vivo) : Negative.

Species : Mouse

OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

OECD Guideline 471 (Bacterial Reverse Mutation Assay)

Ames test (in vitro) : Negative.

With or without metabolic activation.

Species : S. typhimurium TA1535

**11.1.2. Mixture**

**Respiratory or skin sensitisation :**

Contains at least one sensitising substance. May cause an allergic reaction.

**Aspiration hazard :**

May be fatal if swallowed and enters airways.

Aspiration toxicity includes severe acute effects such as chemical pneumonia, varying degrees of pulmonary injury or death following aspiration.

---

## SECTION 12 : ECOLOGICAL INFORMATION

### 12.1. Toxicity

#### 12.1.1. Substances

PARAFFIN WAXES AND HYDROCARBON WAXES (CAS: 8002-74-2)

Fish toxicity : LC50 > 1000 mg/l

Species : Oncorhynchus mykiss

Duration of exposure : 96 h

OECD Guideline 203 (Fish, Acute Toxicity Test)

Crustacean toxicity : EC50 > 10000 mg/l

Species : Daphnia magna

Duration of exposure : 48 h

OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Algae toxicity : ECr50 > 1000 mg/l

Species : Scenedesmus subspicatus

Duration of exposure : 72 h

OECD Guideline 201 (Alga, Growth Inhibition Test)

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS (CAS: 64742-48-9)

Fish toxicity : LC50 > 1000 mg/l

Species : Oncorhynchus mykiss

Duration of exposure : 96 h

Crustacean toxicity : EC50 = 1000 mg/l

Species : Daphnia magna

Duration of exposure : 48 h

Algae toxicity : ECr50 > 1000 mg/l

Species : Pseudokirchnerella subcapitata

Duration of exposure : 72 h

#### 12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

This Safety Data Sheet is prepared in accordance with  
Annex II to Regulation (EC) No 1907/2006

First editing date : 14/12/2001  
Date of last updating : 11/08/2011  
Validation date : 28/03/2014

**12.2. Persistence and degradability****12.2.1. Substances**

PARAFFIN WAXES AND HYDROCARBON WAXES (CAS: 8002-74-2)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS (CAS: 64742-48-9)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

**12.3. Bioaccumulative potential**

No data available.

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Other adverse effects**

No data available.

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

**SECTION 14 : TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2013 - IMDG 2012 - ICAO/IATA 2014).

**14.1. UN number**

1263

**14.2. UN proper shipping name**

UN1263=PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)

**14.3. Transport hazard class(es)**

- Classification :

3

**14.4. Packing group**

III

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

| ADR/RID | Class | Code    | Pack gr. | Label    | Ident.   | LQ          | Provis.      | EQ     | Cat. | Tunnel |
|---------|-------|---------|----------|----------|----------|-------------|--------------|--------|------|--------|
|         | 3     | F1      | III      | 3        | 30       | 5 L         | 163 650 640E | E1     | 3    | D/E    |
| IMDG    | Class | 2°Label | Pack gr. | LQ       | EMS      | Provis.     | EQ           |        |      |        |
|         | 3     | -       | III      | 5 L      | F-E,S-E  | 163 223 955 | E1           |        |      |        |
| IATA    | Class | 2°Label | Pack gr. | Passager | Passager | Cargo       | Cargo        | note   | EQ   |        |
|         | 3     | -       | III      | 355      | 60 L     | 366         | 220 L        | A3 A72 | E1   |        |
|         | 3     | -       | III      | Y344     | 10 L     | -           | -            | A3 A72 | E1   |        |

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

This Safety Data Sheet is prepared in accordance with Annex II to Regulation (EC) No 1907/2006

First editing date : 14/12/2001  
Date of last updating : 11/08/2011  
Validation date : 28/03/2014

## 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available.

---

**SECTION 15 : REGULATORY INFORMATION**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## - Classification and labelling information included in section 2:

The following regulations have been used:

- Directive 67/548/EEC and its adaptations
- Directive 1999/45/EC and its adaptations
- Regulation EC 1272/2008 modified by regulation EC 618/2012
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.

## - Container information:

Packaging to be fitted with child-resistant fastenings (see EC Regulation No. 1272/2008, Annex II, Part 3).

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

## - Particular provisions :

No data available.

## 15.2. Chemical safety assessment

No data available.

---

**SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

## In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Hazard symbols :

Flammable

Contains :

Contains 616-014-00-0 2-OXY-BUTANON. May produce an allergic reaction.

Risk phrase :

R 10 Flammable.

R 66 Repeated exposure may cause skin dryness or cracking.

R 67 Vapours may cause drowsiness and dizziness.

Safety phrase :

S 2 Keep out of the reach of children.

S 46 If swallowed, seek medical advice immediately and show this container or label.

S 23 Do not breathe vapour.

S 24 Avoid contact with skin.

S 51 Use only in well-ventilated areas.

S 62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

## Title for H, EUH and R indications mentioned in section 3 :

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer .

H361d Suspected of damaging the unborn child.

EUH066 Repeated exposure may cause skin dryness or cracking.

R 10 Flammable.

R 11 Highly flammable.

This Safety Data Sheet is prepared in accordance with  
Annex II to Regulation (EC) No 1907/2006

First editing date : 14/12/2001  
Date of last updating : 11/08/2011  
Validation date : 28/03/2014

- R 21 Harmful in contact with skin.
- R 36 Irritating to eyes.
- R 40.C3 Limited evidence of a carcinogenic effect.
- R 41 Risk of serious damage to eyes.
- R 43 May cause sensitisation by skin contact.
- R 63.G3 Possible risk of harm to the unborn child.
- R 65 Harmful: may cause lung damage if swallowed.
- R 66 Repeated exposure may cause skin dryness or cracking.
- R 67 Vapours may cause drowsiness and dizziness.

**Abbreviations :**

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

CMR: Carcinogenic, mutagenic or reprotoxic.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

GHS02 : Flame

GHS07 : Exclamation mark

GHS08 : Health hazard

This Safety Data Sheet is prepared in accordance with  
Annex II to Regulation (EC) No 1907/2006

First editing date : 14/12/2001  
Date of last updating : 11/08/2011  
Validation date : 28/03/2014