

The Solid Wood Flooring Company Unit 1 Helena Court, Hampton Street, Tetbury, Gloucestershire GL8 8JN

Tel: 01666 504015 Fax: 05603 146907 Mobile: 07831 680206

Email:martyn@thesolidwoodflooringcompany.com Web: www.thesolidwoodflooringcompany.com

Thank you for your enquiry. The Green Guide to Specification which is used by architects and specifiers within the UK and Europe to source environmentally sustainable construction products. Green Guide ratings have been compiled for generic building elements which include floor coverings on an as installed basis. Engineered oak floors have been assessed and the ratings are in the screenshot below from our website http://www.thegreenguide.org.uk.

uilding type >	<u>Domestic</u>		
Category >	Floor Finishes		
Element type >	Hard Floor Finishes		
		Element number	Summary rating
14mm Engineered Oak Flooring, 9.29 kg/m2 with adhesive		1321580002	A+
20mm Engineered Oak Flooring, 13.3 kg/m2 with adhesive		1321580001	A+
101		1	
	5_	821580001	В

As you can see the ratings for engineered oak flooring on a scale of A+ to E are at the top end of the scale. You would be able to state in publicity that your products correspond to the rating for the relevant element number but not that the ratings specifically apply to your products. This can only be done with a certified environmental profile which will generate bespoke ratings for your products. Please let me know if you would like more information on this.

Kind Regards

## **Andrew Dutfield**

MSc CCol ASDC CText ATI

Consultant, Centre for Sustainable Products,

BRE, Bucknalls Lane, Watford, Hertfordshire, WD25 9XX

**T** +44 (0) 1923 664 423 **E** <u>dutfielda@bre.co.uk</u> **W** <u>www.bre.co.uk</u>













