



The  
**Solid Wood**  
Flooring Company

## E150UF (ABC) | Technical Datasheet

### Engineered Natural Unfinished White Oak Flooring

#### Sustainability:

The materials used in the construction of our products are not listed in CITES Appendices or on the IUCN Red List of Threatened Species. This is an ethically and sustainably sourced engineered timber wood floor designed for use as an interior floor finish. Engineered wood floors are more sustainable than solid and minimise the impact on valuable resources. Further features are noted below:

- FSC 100% certified
- BRE Green Guide: A+ (Element Number 1321580001)
- Recyclable packaging
- Constructed from natural materials
- Single-component loose-lay installation (no adhesives required)
- Environmental Product Declaration (EPD) available upon request



#### Product Details:

|                     |  |
|---------------------|--|
| Top Layer Species:  | European Oak (Quercus Spp.)  |
| Construction:       | Engineered "3-Layer" White Oak top layer bonded to Black Poplar core & backing   |
| Dimensions:         | 15mm thick (including 4mm top layer) x 240mm wide x 1900mm length  |
| Finish:             | Unfinished ( <i>a finish will need to be applied post fit</i> )  |
| Process:            | Smooth   |
| Grade:              | ABC Select Grade with colour variation and knots ( <i>see grading document for details</i> )   |
| Profile:            | Tongue & Groove  |
| Pattern:            | Single width plank   |
| Edge Profile:       | Square Edged (all four sides)  |
| Slip Resistance:    | Will depend on the finish applied once fitted  |
| Underfloor Heating: | This floor is suitable for underfloor heating  |
| Packaging:          | Recyclable cardboard cartons. Each pack contains 2.736m <sup>2</sup> consisting of:<br>6 boards per pack with 1 board split at 600mm to aid in staggering the layout |
| Weight:             | Each pack weighs 23kgs   |

#### NBS:

|           |                       |
|-----------|-----------------------|
| Uniclass: | Pr_25_71_97_93        |
| CAWS:     | K21/110 Wood flooring |



#### Aesthetics, Characteristics & Samples:

As we use natural materials there will be inherent characteristics such as shade variation, grain patterns, knotting etc. It is the art (and responsibility) of the fitter to re-manufacture the flooring materials to create a finished floor. Small samples will give a representative example of the colour of the finished floor but will not be fully representative of the overall effect. Therefore, should it be necessary to gain a better understanding of how a larger area will look, purchasing cartons for a sample area should be considered, before making a final decision.

## Product Performance:

| Type   | Testing Standard                                       | Results  |
|--|--|--|
| Fire Protection:                               | EN 13501-1 Dn s1                                       | Pass   |
| Thermal Conductivity:                          | EN ISO 12664   | 0.15 W/(mk)  |
| Moisture Content:                              | EN 13183 – 1 (Requirement: 6-9%)                       | (Avg.) 7%  |
| Release of Formaldehyde:                       | Class E1   EN 717 – 1:2006<br>(Requirement: >3 ppm)    | 0.0021 ppm   |
| Slip Resistance:<br>(Based on UV Oiled finish) | BS 7967-2:2002+A1:2013<br>(PTV = Pendulum Test Values) | Dry = 60 PTV (Low risk)<br>Wet = 45 PTV (Low risk) |

|                          |   |
|--------------------------|---|
| Health & Safety          | Engineered wood flooring is a natural product and on its own offers no recognisable health and safety risks. When re-manufacturing any such product into a fitted wood floor please follow HSE advice.  |
| Effects from Moisture:   | Wood flooring will expand if it is exposed to conditions that increases its moisture content beyond 9%. Wood flooring will contract if the prevailing conditions reduce the product moisture content below 6%. Any exposure outside of these parameters will compromise the performance of the product. |
| Expansion & Contraction: | It is a natural process for wood to expand or contract with environmental changes. It is critical to leave sufficient room for expansion.   |
| UV Exposure:             | Wood will be affected by UV light over time, this will cause a change in colour. This is a natural reaction. The intensity will depend on the level of exposure, maintenance routine, usage and inherent characteristics within the timber.   |
| Transmission of sound:   | Where acoustic dampening is required, a specific underlayment should be used. Such options can be discussed with us directly.   |
| Manufacturing:           | Engineered floors are manufactured in accordance with accepted industry standards, which permit a tolerance not to exceed 5%. The variations may be of a manufacturing or natural type (this does not include colour variation).  |

## Storage, Fitting & Maintenance:

Refer to our **Storage, Fitting & Maintenance Instructions** as well as our **T&Cs** for full details.

**Storage:** Wood flooring should be stored flat and away from hazards (i.e. impact damage, excess moisture, heat etc.). 'Wet' trades should be completed before delivery to site to reduce the risk of damages.

**Installation Methods:** All wood flooring must be fitted in accordance with BS 8201:2011.

- Fully bonded: Recommended installation method using SW-890 MS Polymer Adhesive
- Floated: Suitable for floating using our SW-633 underlay

**N.B.** Wood flooring should never be used as a foundation. Therefore, it is important to design any kitchen cabinets (or other heavy furnishing) with their own structural base and not to be sat on the wood floor.

**On-site Protection:** In situations where the flooring is installed but works are to continue afterwards, please ensure the correct protection is used. We advise using BreatherShield® topped with hardboard (taped together, but do not tape the floor). This reduces the chance of surface damage as works continue. **Do not** use rigid plastic coverings.

**Cleaning:** **(Never use solvent or chemical cleaning product)** Correct cleaning and maintenance is critical. Please refer to our Storage, Fitting & Maintenance Instructions for more information.

## Company Approvals:

The Solid Wood Flooring Company operate a stringent sustainable environmental policy, details of which can be seen on the web site. We are certified by all the relevant organisations and our certificate numbers can be seen below:

FSC® - The Solid Wood Flooring Chain of Custody Number: INT-COC-003944-545

PEFC™ - The Solid Wood Flooring Chain of Custody Number: INT-PEFC-COC-1119-545

WWF® - The Solid Wood Flooring Company achieved the highest - 3 Trees - accreditation